

“Device for straightening and closing the rear flap for a self-dimensioning machine for closing parallelepiped boxes”

* * *

DESCRIPTION

5 The present invention refers to a device for straightening and closing the rear flap for a self-dimensioning machine for closing parallelepiped boxes.

 Machines of various kinds for closing the upper flaps of cardboard parallelepiped boxes before applying adhesive sealing tape are known.

10 In particular so-called "self-dimensioning" machines are known, that accept boxes of various widths and heights, automatically adapting their operative parts to the dimensions of the box.

 More in particular self-dimensioning machines are known that comprise a base with support surface for resting the boxes on, a couple of
15 drive belts that can be motorised placed at the two sides of said support surface and that can be brought close to each other to make a drive engagement with the sides of the boxes and a head above said support surface, that carries suitable devices for closing the front, rear and side flaps of the boxes and can be commanded to descend to a rest position for
20 engaging the above-mentioned devices with the upper flaps of the boxes and thus providing for their closure. Suitable mechanical or photocell or other sensors provide for the automation of the various movements in accordance with the position and the dimensions of the boxes.

 One problem encountered by the machines of this type is represented
25 by the closing of the rear flap, that requires a device to take the flap, often partially folded outwards, from behind the flap itself and, after having straightened it, determines the closing of the flap with substantially contrary rotary movement .

 In view of the state of the technique the object of the present invention
30 is to make a device for closing the rear flap for self-dimensioning machines

of the type described above, that permits to carry out in a simple and efficient way first the straightening the flap from a position partially folded outwards and then the rotation of the same flap for reaching the closing position.

5 In accordance with the invention this object is achieved with a device for closing the rear flap in a self-dimensioning machine for closing the upper flaps of parallelepiped boxes of the type comprising a base with surface for supporting the boxes, a couple of drive belts that can be motorised placed at the two sides of said support surface and that can be brought close to each
10 other to make a drive engagement with the sides of the boxes, a head above said support surface, that carries devices for closing the front, rear and side flaps of the boxes and can be commanded to descend from a rest position to engage the above-mentioned devices with the upper flaps of the boxes and provide for their closure, and means for detecting the position and the
15 dimensions of the boxes for the automatic command of the movements of the machine , characterised in that it comprises a rod for straightening the rear flap, that is pivoted on said head and can be commanded to rotate from a substantially horizontal rest position to a vertical working position and to translate in the same feed direction of the boxes to carry out the
20 straightening of the rear flap, a vertically mobile touching group that can be commanded to descend towards said support surface up to a position depending on the height of the box and a lever pivoted on said touching group downstream from said straightening rod and flexibly kept in an angular rest position suited to meeting with one of its inclined planes, during
25 the descent of the touching group, the straightened rear flap and thus to cause the movement of the flap to the closing position.

 In this manner, whatever the height of the box is, first the rear flap is straightened from an eventual position folded outwards and then it is folded to the closing position. Thus the certainty of effective and complete closing
30 of the box is obtained, whatever its height is.

In particular it is to be noted that the closing movement of the rear flap is not imposed by a power command, but it is simply the result of the flap-closing lever meeting the flap itself during the descent of the touching group.

5 An embodiment of the present invention is illustrated as non-limiting example in the enclosed drawings, in which:

Figure 1 shows in a side view, in the position awaiting a box, a machine for closing parallelepiped boxes that uses a device for straightening and closing the rear flap in accordance with the present invention;

10 Figure 2 shows the same machine in a front view, again in said awaiting position;

Figure 3 shows the same machine, again in said awaiting position, sectioned in a plan above the feed surface of the boxes;

15 Figure 4 shows the machine in a side view at the moment the box enters;

Figure 5 shows the machine in a front view in the working position of Figure 4;

Figure 6 shows the machine in a side view immediately after the entrance of the box;

20 Figure 7 shows the machine in a front view in the working position of Figure 6;

Figure 8 shows the machine in a side view in a successive phase of feed of the box;

25 Figure 9 shows the machine in a front view in the working position of Figure 8;

Figure 10 shows the machine in a side view at the moment the front flap of the box is straightened;

Figure 11 shows the machine in a side view at the moment the closing movement of the front flap of the box starts;

30 Figure 12 shows the machine in a side view at the moment the rear

flap of the box is straightened;

Figure 13 shows the machine in a front view in the working position of Figure 11;

5 Figure 14 shows the machine in a side view at the beginning of the closing movement of the rear flap of the box;

Figure 15 shows the machine in a front view in the working position of Figure 13;

Figure 16 shows the machine in a side view at the end of the closing movement of the rear flap of the box;

10 Figure 17 shows the machine in a front view in the working position of Figure 16;

Figure 18 shows the machine in a side view at the end of the closing movement of the front flap of the box;

15 Figure 19 shows the machine in a front view in the working position of Figure 18;

Figures 20-24 show enlarged details of several mechanisms comprised in the machine of the previous figures.

20 The machine shown in the drawings is provided for the straightening and the closing of the end flaps, front and rear, of parallelepiped boxes fed in succession onto a support surface 1 formed by a succession of idle rollers 2 supported by a base frame 3 (fig. 3).

25 The succession of idle rollers 2 is preceded, in the feed direction of the boxes (from right to left looking at Fig. 1), by a motorised roller 4 in turn preceded by a stopping blade 5, that can be raised and lowered by activating a pneumatic cylinder 6.

At the two sides of the support surface 1 two chain conveyors 7 are provided that can be motorised thanks to an electric motor 8, and that can be brought closer to each other or further away from each other by means of the use of any device known in itself.

30 From the base frame 3 two fixed portals 9 and 10 extend upwards, the

first of which supports, on one part, a succession of photocells 11, 12 and 13 and, on the other side, a corresponding succession of mirrors 14, 15 and 16 capable of reflecting backwards the light rays emitted by the above-mentioned photocells (Figures 1 and 2).

5 The fixed portal 9 also supports along its side uprights a couple of guide rods 17 for the vertical sliding of a mobile portal 18, that can be raised and lowered by means of a pneumatic cylinder 19 placed along one of its above-mentioned uprights. A brake group 20 is provided for, whose task is to stop the descent of the mobile portal 18 when required. A couple of bars
10 21 is fixed to the mobile portal 18, and bear photocell 22 and a facing mirror 23. A notch reader 24 is also fixed to one of the two bars 21 and cooperates with a holed band 25 that extends vertically along one of the uprights of the fixed portal 9 (Figures 1 and 2). The constructive details of the notch reader 24 and the holed band 25 are shown in enlarged scale in Fig. 20.

15 The mobile portal 18 also bears centrally a head or trolley hollow internally 26, on which a rod 28 is pivoted in 27 destined to straightening and folding the front flap of the boxes. The rod 28 is clutched by means of a pneumatic cylinder 29 fitted with pressure regulator (not shown), that shows resistance to the rotation of the rod 28 in relation to the normal vertical rest
20 position that is illustrated in Figures 1 and 2. The constructive details of the pin 27, of the rod 28 and of the cylinder 29 are shown in enlarged scale in Figures 21 and 22, where Figure 22 is a section view according to the line XXII-XXII of Figure 21.

 The trolley 26 also bears, sliding on a horizontal splined pin 30 thanks
25 to a splined bushing 31, a rod 32 destined to straightening and folding the rear flap of the boxes. The splined pin 30, and with it the bushing 31 and the rod 32, is commanded to rotate from the nearly horizontal position of Fig. 2 to the vertical position of Figures 12 and 13 by a pneumatic cylinder 33 to which an end of stroke sensor 34 is associated, while the translation of the
30 bushing 31, and thus of the rod 32, along the splined shaft 30 from the

backward position of Fig. 1 to the forward position of Fig. 14 is commanded by a pneumatic cylinder 35 to which an end of stroke sensor 36 is associated. The constructive details of the 30, of the bushing 31, of the rod 32 and of the cylinders 33 and 35 with relative sensors 34 and 36 are shown in enlarged scale in Figures 23 and 24, where Figure 24 is a right view in relation to Figure 23.

The fixed portal 10 bears in turn a touching group 37, that can be moved vertically along guide rods 38 by means of a pneumatic cylinder 39 with brake group 66 (Fig. 1) and bears a notch reader 40 cooperating with a vertical fixed holed band 41. The notch reader 40 and the holed band 41 are all similar to the reader 24 and to the holed band 25 shown in Fig. 20.

The touching group 37 also bears an L lever 42, pivoted in 43 (Fig. 1), whose task is to carry out the closing folding of the rear flap of the boxes and is connected by means of a pin joint 44 to the stem of a pneumatic cylinder 45 fitted with end of stroke sensor 46.

Finally a central longitudinal guide 49 is pivoted in 68 on the touching group 37, and is also connected at the rear to the same touching group 37 by means of a connecting rod 50 pivoted in 51 and 52, with which a spring 53 reacts. The guide 49 is normally in a slightly inclined position in relation to the horizontal one (Fig. 1), but can be moved to a horizontal position (Fig. 18) by activating a pneumatic cylinder 47 to which it is connected by means of a pin joint 48.

Through effect of the structure described above the machine illustrated in the drawings operates in the following manner on a parallelepiped cardboard box 60, which is presented with upper flaps open, and in particular with front flap 61 and rear flap 62 partially rotated outwards as shown in Fig. 4, on a sliding surface 63 placed in continuation of the support surface 1.

The first phase of the working cycle of the machine shown in the drawings is illustrated in Figures 4 and 5. The box 60 coming from the

sliding surface 63 arrives at the entrance of the machine, where it stops against the stop 5, and activates the photocell 11, whose command starts the cycle.

5 The activation of the photocell 11 starts off the detection of the box height. With the photocell 22 free, the trolley 26 carrying the photocell 22 starts the descent, guided by the rods 17 and commanded by the pneumatic cylinder 19, until the photocell 22 is activated. During the descent of the trolley 26 the notch reader 24, in one with the trolley 26, detects by means of the holed band 25 the height position of the trolley itself. When the photocell
10 22 detects the box 60, the descent of the trolley 26 is blocked by means of the activation of the brake group 20.

 The activation of the photocell 22 commands the entrance into the machine of the box 60 lowering the stop 5, activated by the cylinder 6, and starting the motorised roller 4 and the motor 8. At the same time the
15 touching group 37 starts getting closer to the box 60 under the command of the pneumatic cylinder 39 and with the guide of the rods 38 (Figures 6 and 7). By means of the notch reader 24 and the relative holed band 25 the height at which the trolley 26 is stopped is known. The notch reader 40 with respective holed band 41 enables the position of the touching group 37 to be
20 controlled and temporarily stops the descent at about 10 cm from the box; this is done to make the machine cycle faster. The box 60 advances, driven by the motorised roller 4, until the photocell 12 (Fig. 8) is activated.

 The activation of the photocell 12 commands the closing of the driving
25 belts 7, which, coming into contact with the sides of the box 60 and being the same in movement by means of the motor 8, drive the same inside the machine.

 During its advancement the box 60 activates the photocell 13, which in
this phase does not activate any function, and comes into contact with the
rod 28, which at first straightens the front flap 61 of the box (Fig. 10) and
30 successively starts folding it inwards (Fig. 11). During rotation, the rod 28

extends the cylinder 29 (Fig. 21), which opposes resistance, can be regulated by means of special pressure regulator, that enables the front flap of boxes of different hardness to be folded. During the advancement the box 60 frees the photocell 11, which by means of the cylinder 6 commands the raising of the stop 5 in order to block the entrance of the successive box 65 into the machine (Fig. 12).

The box 60 continues advancing until it frees the photocell 13, which commands the stop of the motor 8 and therefore of the box 60. At this point the front flap 61 of the box 60 has been almost completely folded inwards and at the same time when the box stops the straightening the rear flap 62 starts up. The rod 32 destined to straightening the rear flap 62 is activated by the pneumatic cylinder 33 so as to go to the almost horizontal rest position of Fig. 2, suitable for enabling the passage of the boxes, to the vertical position of Fig. 13. Reaching the vertical position, the sensor 34 activates the pneumatic cylinder 35, that command the translation of the splined bushing 31, and thus of the rod 32, along the splined shaft 30 from the position illustrated in a continuous line in Fig. 23 to that illustrated in dots and lines in the same figure. The rod 32 thus straightens the rear flap 62.

When the translation has been made, the sensor 36 associated to the pneumatic cylinder 35 commands the activating of the pneumatic cylinder 39 for the descent of the touching group 37 for detecting the height of the box. The touching group 37 starts the descent and by means of the inclined surface 69 of the lever 42 starts folding the rear flap 62 inwards (Figs. 14 and 15).

During the descent of the touching group 37 the lever 42 continues rotating and folding the rear flap 62 and at the same time commands the return of the pneumatic cylinder 45. When the lever 42 reaches the horizontal position corresponding to the completion of the closing of the rear flap 62 of the box 60, the magnetic sensor 46 associated to the pneumatic

cylinder 45 detects the complete return of the latter and consequently, in combination with the reader 40 and the holed band 41, determines the detection of the height of the box (Figs. 16 and 17).

5 The magnetic sensor 46 also commands the stopping of the descent of the touching group 37, by activating the brake group 66, and through the pneumatic cylinder the lowering of the rear part of the central guide 49, which positions itself horizontally and thus causes the completion of the closing of the front and rear flaps 61 and 62 (Figs. 18 and 19). The connecting rod 50 and the spring 53 make the guide 49 tilting so as to also
10 permit the passage of any over-filled boxes. The magnetic sensor 46 also commands the complete rotation of the rod 28 for folding the front flap 61 so as to disengage it from the box, the repositioning of the rod 32 for folding the rear flap 62 and the restart of the motor 8 and of the belts 7 for starting the box 60 again. In this phase, by means of the notch reader 40 and the
15 relative holed band 41, the positioning of the touching group 37 is detected, definitively, and consequently the height of the box 60 to transmit to the successive station, that provides for the closing of the side flaps 67 of the box 60 and the application of the sealing tape at the top of the box.

20 The whole set-up then returns to the initial position of Fig. 1. To prevent useless excursions of the trolley 26, and therefore increase the productivity of the machine, the positioning of the trolley 26 comes about with the following logics:

- photocell 11 activated: box present at machine input;
- photocell 22 activated: the box in input has a height exceeding that of
25 the position of the trolley 26, for which the latter rises until the photocell 22 is deactivated;
- photocell 22 deactivated, the box in input has a lower height than that of the position of the trolley 26, for which the latter lowers until the photocell 22 is activated;
- 30 – photocell 11 deactivated: no box in waiting at machine input and

therefore the trolley 26 rises up to the upper limit switch. When the height of the box is detected, the cycle starts up again as has already been described.